



## 986/316

### VALVOLA DI RITEGNO

- CHECK VALVE
- RÜCKSCHLAGVENTIL
- VANNE AVEC CLAPET ANTI-RETOUR
- VÁLVULA DE RETENCIÓN

**MATERIAL:** AISI 316 - 1.4401

**NOTE:** impiego acqua (no gas)

CODE	DN	DN inch	A mm	B mm	C mm		
986104316	8	1/4"	18	55	32	1	94
986308316	10	3/8"	20	55	32	1	91
986102316	15	1/2"	25	55	32	1	93
986304316	20	3/4"	29	70	44	1	129
986100316	25	1"	36	84	53	1	191
986114316	32	1 1/4"	45	99	62	1	281
986112316	40	1 1/2"	51	119	78	1	388
986200316	50	2"	64	123	89	1	704
986212316	65	2 1/2"	80	147	113	1	1425
986300316	80	3"	93	166	132	1	2085
986400316	100	4"	120	193	167	1	3415

- Valvola di ritegno in acciaio inox tornito (Dim. 1/4" - 3/8" - 1/2")

- Valvola di ritegno in acciaio inox stampato (Dim. 3/4" - 1" - 1 1/4" - 1 1/2" - 2" - 2 1/2" - 3" - 4")

- Corpo e parti metalliche in acciaio inossidabile AISI 316; - Tenuta: FPM; - Connessioni filettate femmina: ISO 228/1 (ex DIN 259) femmina cilindrica;

- Pressione di apertura: max 0,03 bar - min 0,025 bar; - Pressione di lavoro: 16 bar; - Temperatura di esercizio: -20°C + +150°C

- Stainless steel turned check valve (Dim. 1/4" - 3/8" - 1/2")

- Stainless steel molded check valve (Dim. 3/4" - 1" - 1 1/4" - 1 1/2" - 2" - 2 1/2" - 3" - 4")

- Body and fittings in stainless steel AISI 316; - Seal: FPM; - Threaded female: ISO 228/1 (ex DIN 259) female cylindrical;

- Opening pressure: 0,03 bar max - min 0,025 bar; - Working pressure: 16 bar; - Operating temperature: -20°C to +150°C