




ISO 4144

**145L****VITE DOPPIA RIDOTTA**

- HEXAGONAL NIPPLE REDUCED
- 6-KANT DOPPELNIPPEL REDUZIERT
- MAMELON RÉDUIT
- MACHÓN REDUCIDO

**MATERIAL:** AISI 316 - 1.4401**DIMENSION:** ISO 4144**THREAD:** EN 10226-1 (ex ISO 7/1)**RATING:** 150 PSI - PN10

CODE	DN1 inch	DN2 inch	L mm	SW mm	 g		
145104108L	1/4"	1/8"	22,5	15	13	10	1500
145308108L	3/8"	1/8"	24	18	26	10	750
145308104L	3/8"	1/4"	26,5	18	21	10	900
145102104L	1/2"	1/4"	30	22	32	5	500
145102308L	1/2"	3/8"	30,5	22	32	5	500
145304104L	3/4"	1/4"	31,5	28	46	5	300
145304308L	3/4"	3/8"	32	28	47	5	300
145304102L	3/4"	1/2"	35,5	28	54	5	300
145100102L	1"	1/2"	38,5	35	85	5	200
145100304L	1"	3/4"	39,5	35	89	5	200
145114102L	1 1/4"	1/2"	41,5	43,5	117	5	120
145114304L	1 1/4"	3/4"	42,5	43,5	119	5	120
145114100L	1 1/4"	1"	45	43,5	129	5	120
145112304L	1 1/2"	3/4"	42,5	49,5	144	5	75
145112100L	1 1/2"	1"	45	49,5	157	5	75
145112114L	1 1/2"	1 1/4"	47,5	49,5	169	5	75
145200100L	2"	1"	50	62	252	5	50
145200114L	2"	1 1/4"	52,5	62	272	5	50
145200112L	2"	1 1/2"	52,5	62	296	5	50
145212100L	2 1/2"	1"	52	77,5	405	2	24
145212114L	2 1/2"	1 1/4"	54,5	77,5	271	2	24
145212112L	2 1/2"	1 1/2"	54,5	77,5	435	2	24
145212200L	2 1/2"	2"	59	77,5	454	2	24
145300112L	3"	1 1/2"	58	90,5	559	1	20
145300200L	3"	2"	62,5	90,5	633	1	20
145300212L	3"	2 1/2"	64,5	90,5	614	1	20
145400200L	4"	2"	69	116	1133	1	10
145400212L	4"	2 1/2"	71	116	1044	1	10
145400300L	4"	3"	74	116	1398	1	10